



www.lemo.com

SUMMARY

Wires

 Low
 0

 High
 0

 Coax
 1

 Triax
 0

 Quad
 0

 Fiber
 0

Series 00

Termination type Coupler/adapter/bridge

0

IP rating 50

Cable Ø 0.00 - 0.00 mm

Matching parts

Fluidic

Status

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model FTA*: T-plug with two in line receptacles

Keying Circular (can rotate)

Housing Material Brass (nickel plated) shell, collet nut, latch sleeve and mid pieces

Cable Fixing p 0 - 0 mm

Variant

Performance

Configuration 0.25 : 1 Coax (50 Ohm)

Insulator T: PTFE Rated Current 4 Amps

Specifications

Contact Type: Coaxial 50 Ohm

Max. Matings: 5000

Test voltage: 1.1 kV (rms)


Others

Endurance (Shell): 5000 mating cycles

F ret (min): 100 N IP Rating: 50

DRAWINGS

Draws



Dimensions

	А	Н	I	L
mm.	9	17.5	9.5	30
in.	0,35	0,69	0,37	1,18

RECOMMENDED BY LEMO

Tools

None

Cables