


PLUGSERIES
POZ 24VDC/24VDC 5A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com



The modular kit-type system represents a new generation of plug-in optos.
At the heart is an innovative PXS or PXZ relay base. The PLUGSERIES is particularly service-friendly and the ideal link between SSR and the application. Conventional SSR and LED indicators are simply plugged in, retaining and disassembly clips provide a secure fixing. Pre-assembled SSR couplers round off the product range. Plug-in ZQV 2.5 cross-connectors enable multiplexers to be set up quickly thanks to simple side-by-side mounting.

General ordering data

Order No.	8610970000
Part designation	POZ 24VDC/24VDC 5A
Version	PLUGSERIES, Solid-state relay, 0...30 V DC, 5 A, Tension clamp connection
GTIN (EAN)	4032248271757
Qty.	10 pc(s).

**PLUGSERIES
POZ 24VDC/24VDC 5A**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Technical data

Dimensions

Length	92 mm	Width	15.3 mm
Height	87 mm	Weight	18 g

Temperature

Storage temperature	-40 °C...+50 °C
---------------------	-----------------

Approvals

Approvals institutes	GOSTME25; CE; CURUS
----------------------	---------------------

Control side

Power rating	250 mW	Rated auxiliary voltage	No
Rated control voltage	15 V DC...30 V DC		

General data

Standards	EN 50178	Humidity	40°C / 93% rel. humidity, no condensation
Conductor connection system	Tension clamp connection	DIN Rail compatibility	TS 35
Solid-state type	POWER MOS-FET		

Insulation coordination (EN 50 178)

Clearance and creepage distances for control/load side	> 8 mm	Overvoltage category	III
Pollution severity	2	Protective separation acc. to VDE 0106	No
Rated impulse withstand voltage	2.5 kV _{eff}	Rated voltage	300 V

Load side

Protective circuit, load side	Integrated free-wheel diode	Rated auxiliary voltage	No
Rated switching current	5 A	Rated switching voltage	0...30 V DC
Short-circuit-proof	No	Status indicator load side	Green LED
Switch-off delay	18 ms	Switch-on delay	2 ms
Voltage drop at max. load	≤ 0.3 V		

Classifications

eClass 6.0	27-27-09-90
------------	-------------

Datasheet

**PLUGSERIES
POZ 24VDC/24VDC 5A**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Drawings

Electric symbol

